
University Endowment Lands

Integrated Stormwater Management Plan

Stage 3 & 4 Reports















Agenda

- 1. Work completed to date
- 2. Stage 3 Report Summary
- 3. Stage 4 Report Summary
- 4. Discussion

Work completed to date







UEL ISMP Approach

Stage	Question Answered	Description of tasks	Relevant ISMP Sections
1	What do we have?	Review background information and summarize existing conditions	 Study Area Regulatory Context Land Use Hydrology Stormwater System Hydrogeology and Soils Environment Hydraulic Modelling and Assessment
2	What do we want?	Establish the vision for future development	- Vision and Goals
3	How do we put this into action?	Development of an implementation plan, funding and enforcement strategies	- Implementation Plan
4	How do we stay on target?	Development of a monitoring and assessment program	- Adaptive Management Plan





Stormwater Management Vision and Goals





"A stormwater management plan that protects the natural and built environment through enhancement of natural watercourses, and provides opportunities for collaboration and engagement with community and residents on stormwater issues"





Stormwater Management Vision and Goals

Goal 1: The UEL community is engaged in stormwater management

Goal 2: Healthy streams and a natural environment are a part of the UEL

Goal 3: Stormwater infrastructure provides an adequate level of service, while protecting life and property

Goal 4: The UEL provides guidelines and a regulatory framework for stormwater management

Goal 5: Stormwater management at UEL adapts to change

Comments from Stage 2 Report?

Stage 3

Development of an Implementation Plan





UEL ISMP Stage 3 Development of an Implementation Plan

10 Action Items were identified and are proposed for implementation to help the UEL meet the goals and the vision established in Stage 2



Action Item #1:

Promote stormwater management awareness and engagement opportunities

 Promote Spanish Bank Streamkeepers



 Retain all stormwater reports and study results on record






Action Item #2:

Continue to implement UEL's combined sewer separation strategy


- Currently in implementation phase of separating existing combined sewers in Area B
- Sewer separation helps reduce combined sewer overflows, sewage backups, and negative impact on baseflows in the Acadia Creek
- Opportunity to implement BMPs, such as rain gardens, to manage stormwater efficiently





Action Item #3:

Manage the quantity of road runoff





Action Item #3:

Manage the quantity of road runoff

- Reduce impact of increased impervious areas
 - Decrease stream erosion
 - Groundwater recharge
 - Increased stream baseflows
- Rain gardens provide a plausible solution



Action Item #4:

Upgrade stormwater treatment at the UEL Works Yard








Action Item #4:

Upgrade stormwater treatment at the UEL Works Yard






Action Item #5:

Identify stormwater infrastructure that are poorly located for maintenance. Develop plans for management or replacement.

(i.e. the 300mm diameter storm sewer in Pacific Spirit

Park east of Acadia Road)







Action Item #6:

Continue to upgrade system capacity and renew aging infrastructure in a proactive manner through the capital planning process

Project Reference Number	Description
2015-02	Construction of stormwater/sanitary sewer separation on Wesbrook Cres, north of Chancellor Blvd.
2016-02	Construction of storm sewer replacement on Wesbrook Cres. South of Chancellor Blvd.
2016-01	Construction of new storm sewer on Alison Rd between Campus Rd. and College Highroad, and on Western Parkway between College Highroad and University Blvd.
2017-02	Design and construction of storm sewer replacements on lane north of College Highroad
2018-01	Construction of sanitary/stormwater separation on Acadia Rd. north of Chancellor Blvd.
2018-02	Design and construction (reline) of storm sewer on Drummond Dr. and College Highroad
2021-01	Construction of Water, Sewer and Road replacement on Newton Wynd between Acadia Rd. and Kingston Rd.
TBC-02	Construction of storm sewer replacement on lane north of Wycliffe Rd.

Action Item #7:

Develop mitigation measures to address slope stability in Area B



Action Item #8:

Integrate stormwater asset maintenance with work order management using a GIS-centric system





Action Item #9:

Develop Erosion and Sediment Control requirements





BULLETIN 2002-003-EV March 1, 2017
EROSION AND SEDIMENT CONTROL LARGE LOT DEVELOPMENTS (1,000M² OR MORE) (Revised)

EROSION AND SEDIMENT CONTROL (ESC) MONITORING CRITERIA

Applicable Bylaw	Sewer and Watercourse Bylaw No. 8093 (the Bylaw)
pH Requirements	Discharge water to have a pH of 6.0-9.0
Turbidity Requirements	Discharge water Total Suspended Solids (TSS) not to exceed 75mg/L.
Environmental Monitoring	Must be completed by a Qualified Person (QP). Acceptable designations include Applied Science Technologist (ASc.T), Environmental Professional in Training (EPt) or EP, BC Certified Erosion and Sediment Control Lead (CESCL) or equivalent, Engineer in Training (EIT), Professional Engineer (P. Eng), and Biologist in Training (BIT) or higher.
	Dry Season (May-Sept): Bi-weekly Wet Season (Oct-Apr): Weekly
	Additional monitoring is required within 24 hours of a significant rainfall event (SRE) (>25 mm in 24 hrs). Additional monitoring is no required if the SREs are within 48 hours of each other.
Monitoring Frequency	Discharge water sampling can cease once the Site is connected to the City sewer system or with written approval from Environmental Protection. Monitoring of best management practices should continue for the duration of the project.
	Monitoring frequency can be modified upon agreement in writing between the City Inspector and the Contractor or QP. Samples will be submitted for laboratory analysis of TSS if field testing results exceed the Trigger Value of 45 nephelometric turbidity units (NTU)**
Sampling Parameters	The Environmental Monitor may be permitted to submit a Site specific calibration curve to the City if analytical results are consistently below 75 mg/L.
	If the field measurements exceed 45 NTU or if the pH is less than 6.0 or greater than 9.0, the Contractor must cease discharge until appropriate remedial measures have been undertaken. Templated report submitted within 48 hours of the monitoring event
	for Sites which are out of compliance.
Report Submission	Templated report submitted within 7 days of the monitoring event for Sites which are in compliance. If laboratory analysis is required, the analytical results must be submitted within 7 calendar days.
	Reports are to be submitted to: environmentalprotection@vancouver.ca
Site Maintenance	No sediment-laden water from the work site shall be pumped out or otherwise discharged directly to a storm sewer system, water course, or other drainage system in such a manner as to bypass the sediment control system.
	Deficiencies identified by the Environmental Monitor are to be resolved as soon as practically possible.
Removal/Alterations of Treatment Works	No changes to the water treatment system are to be made without the City's Environmental Protection approval. A written request must be approved by Environmental Protection. A Site inspection may be required prior to approval.


DOC/2016/359505 Page 2 of



Action Item #10:

Control runoff from private properties

- Review and formalize stormwater discharge limits for developments
- Provide options for developers for limiting stormwater runoff





Summary of Stage 3 Action Items

- 1. Promote stormwater management awareness and engagement opportunities
- 2. Continue to implement UEL's combined sewer separation strategy
- 3. Manage the quantity of road runoff
- 4. Treat stormwater runoff from the UEL Works Yard
- 5. Decommission, where possible, pipes that are poorly located for maintenance and replacement (i.e. the 300mm diameter storm sewer in Pacific Spirit Park east of Acadia Road)
- 6. Continue to upgrade system capacity and renew aging infrastructure in a proactive manner through the capital planning process
- 7. Establish areas of no infiltration at the UEL so as not to threaten slope stability
- 8. Integrate stormwater asset maintenance with work order management using a GIS-centric system
- 9. Develop Erosion and Sediment Control requirements
- 10. Control runoff from private properties

Stage 4


Adaptive Management Plan






Metro Vancouver's Monitoring and Adaptive Management Framework

Recommended Monitoring Programs





Monitoring Watershed Health





Adaptive Management

Assessment of Watershed Health Monitoring Results

- Water Quality Results
- Flow Monitoring Results
- Benthic Invertebrate Sampling Results



Adaptive Management

Assessment of Watershed Health Monitoring Results

For Example,

Water Quality Assessment Criteria (MAMF, 2014)

	Good Level	Catiofactery Layel	Need Attention Level
	Good Level	Satisfactory Level	Need Attention Level
General Parameter			
Dissolved Oxygen (mg/L)	≥ 11	6.5 to < 11	< 6.5
рН	6.5 to 9.0	6.0 to < 6.5 or > 9.0 to 9.5	< 6 or > 9.5
Water Temperature (° C)			
Low flow summer	< 16	16 to 18	>18
Wet Weather	7 to 12	5 to <7 or >12 to 14	< 5 or > 14
Conductivity (µS/cm)	< 50	50 to 200	> 200
Turbidity (NTU)	≤ 5	> 5 to 25	> 25
Nutrients			
Nitrate as Nitrogen (mg/L)	≤ 2	2 to 5	> 5
Microbial Parameters			
E.coli (freshwater) (CFU/100ml)	Geomean ≤ 77	Geomean between 78 - 385	Geomean > 385
Fecal coliform (CFU/100ml)	Geomean ≤ 200	Geomean between 2201 - 1,000	Geomean > 1,000
Metals (Total Metals) (μg/L)			
Iron	< 800	800 to 5,000	> 5,000
Cadmium	< 0.06	0.06 to 0.34	> 0.34
Copper	< 3	3 to 11	> 11
Lead	< 5	5 to 30	> 30
Zinc	< 6	6 to 40	> 40



Adaptive Management Practices

- Source Control Measures
 - Absorbent Landscaping
 - Rain Gardens
 - Pervious Pavement, and etc.
- Education and Public Outreach
- Cross Connection Control
- Runoff Detention, Retention, and Treatment Facilities
- Riparian Habitat Restoration
- Mitigation of Construction Impacts



Stage 4 Report In Summary

- 1. Monitor watershed health at strategic locations
- 2. Evaluate results of monitoring according to available criteria
- 3. Adapt to changes in watershed health through implementation of Adaptive Management Practices

Thank You!

Discussion and Questions

